




Features

- Plug-and-Play
- Support start-up screen
- RS-485 Interface
- Full support MA-1188/1189 series controller
- Resolution : 192×64 pixels
- Dual watchdog timer
- Surge, EFT and ESD protection
- Brightness : 60cd/m²

Order example



Specification

Model	MATP
Screen type	4.3" STN-LCD
Display color	Monochromatic
Backlight	Automatic turn off time is 5 sec (On = do not turn off)
Resolution	192 × 64 pixels
Display range	96 × 32 mm
Start-up screen size	108 × 64 Bmp
Interface	RS-485
Input power	10 ~ 30 VDC
LCM life	50,000 hours
Brightness	60 cd/m ²
Contrast	Adjustable resistor
Cooling method	Natural air cooling
Operation temperature	- 10~ + 60°C (No freezing)
Storage temperature	- 20~ + 70°C (No freezing)
Size (L × W × H)	158 × 87 × 29 mm

Application software



Mindman editor

- Support Model: MA series distributed control system
- Support OS: Windows 98 / ME / 2000 / XP / Vista / Window7



Mindman utility

- Support Model: MA series distributed control system / MA series remote modules
- Support OS: Window98 / ME / 2000 / XP / Vista / Window 7



MA-152*U driver / AMB128 driver

- Support Model: MA series industrial communication/ MA series memory card
- Support OS: Window98 / ME / 2000 / XP / Vista (32/64 bit) / Window 7(32/64 bit) / WinCE / Linux / Mac




MA-1571U driver

- Support Model: MA series industrial communication
- Support OS: Window98 / ME / 2000 / XP / Vista (32/64 bit) / Window 7(32/64 bit) / WinCE / Linux / Mac / Window Server 2008 R2 / Android

Accessories


ADP090401

- All type
- Adapter board




USB1800

- MA series converter
- USB cable




AMB128

- MA series DCS series
- Memory card



DSCAB

- MA series DCS series
- Adapter cable



Applicable model

MA-1188*, MA-1189*
MA-1520, MA-1521,
MA-10**,
MA-3016

MA-1520U, MA-1521U,
MA-1571U

MA-1188*, MA-1189*

MA-1188*, MA-1189*